CMPE 108 - Experiment 4
Repetitive Structures

OBJECTIVES:

- Understand how to edit, compile and execute C computer codes.
- Understand C programming: repetitive structures

NOTES:

- You should prepare the preliminary work before coming to the laboratory session and bring soft or hard copies of the preliminary work with you.
- Before writing a computer code, you should do the following steps:
  1) understand and analyze the problem,
  2) develop an algorithm and/or flowchart,
  3) convert the algorithm and/or the flowchart into a C code.

PRELIMINARY WORK:

1. Trace the following code segments and show the output:

a)
```
int i = 1;
while (i++ < 5){
   printf("%d ", i);}
```

b)
```
int i = 1;
while (++i < 5){
  printf("%d ", i);}
```

Note the difference between a) and b).

c)
```
int i = 1;
while (i <= 4)
{  printf("  *  \n");
   printf(" *** \n");
   printf("*****\n");
   printf("  *  \n");
   printf("  *  \n\n");
   i++;   }
```

d)
```
int i = 1;
do
{  printf("  *  \n");
   printf(" *** \n");
   printf("*****\n");
   printf("  *  \n");
   printf("  *  \n\n");
   printf("\n");
   i++;
} while(i <= 4);
```

Note the difference between c) and d).

e)
```
int i;
for (i=0; i<5; i++)
  { printf("%d ",i);}
```

Re-write this loop using while-loop and do-while loop.

f)
```
int i;
i=0;
while (i<5) {
  printf("%d ", i);
  t++;}
```

if you delete i++; what will happen? What kind of loop you will have?

g) How can you make the for-loop to be infinite? Refer to part f

h)
```
for(int i=1; i<8; i++)
{ if (i==4) break;
  printf("%d ", i);}
```

Can you re-write this code-segment without break statement?

i)
```
for(int i=1; i<8; i++)
{    if (i==4) continue;
     printf("%d ", i); }
```

Can you re-write this code-segment without continue statement?

TASKS during the LAB hours:

1. Consider the following code that finds the sum of all integers between 1 and the number N:

```
#include<stdio.h>
#include<math.h>
int main()
{
      int N,i, sum=0;
      printf("Enter an integer number: ");
      scanf("%d",&N);
      for(i=1;i<=N;++i)
            sum=sum+i;
      printf("The sum=%d\n", sum);
      return 0;
}
```

a) Edit, compile and execute this code. Use the following input values for N: **10**.

b) Modify the given code to read the value of N and find and prints the sum of the even numbers only.

Note: a number i said to be even if it can be divided by 2 without a remainder, i.e., i%2=0

A sample run of the program must be as follows:

```
Program to find sum of even numbers between 1 and  N
Enter an integer number N:  10
The sum of even numbers is 30.
```

c) How can you modify part b to find the average of the even numbers only?

2. Write a C program that calculates the average of N different positive integers and prints the value of N and average on the screen using,

(a) *while* loop structure
(b) *do-while* loop structure.

Note: Write a separate C program for each part.

3. The GPA of a student taking 5 courses is calculated as

$$\text{GPA}=\frac{\sum_{i=1}^{5} p_i * cr_i}{\sum_{i=1}^{5} cr_i}$$

where cr_i and p_i are, respectively, the credit and the points of the i^{th} course. The points indicate how well a student has done in a particular course and vary depending on the letter grade received from that course. More formally, the points are calculated according to the following table:

Letter grade	Points
A	4
B	3
C	2
D	1
F	0

You are asked to write one C code to calculate the GPA of 30 students in the class. Assume that all students are taking 5 courses and the letter grade is calculated according the student's course average as

80≤average≤100	letter grade=A
70≤average<80	letter grade=B
60≤average<70	letter grade=C
50≤average<60	letter grade=D
Otherwise	letter grade=F

where, the average is computed as:

```
average=0.5*final+0.4*midterm+0.1*lab.
```

You are asked to write a C code to do the following:

1) For each student calculate the GPA.
2) Find the highest GPA, and the lowest GPA.

Note: The lab, the midterm and the final grades for each student course can be entered as inputs from the keyboard.